

[illegible]

00634243-080800

a fingerprint by pinpointing with the light emitted from the illumination device and making the light receiving device pinpoint-receive the light reflected by the fingerprint, and thereby obtaining an image of the fingerprint.

According to the first aspect of the invention, the fingerprint is pinpoint-irradiated with the light through the active matrix liquid crystal cell, and the reflected light is received through the light guiding plate, whereby the image of the fingerprint can be easily obtained.

According to a second aspect of the present invention, the fingerprint reading device according to the first aspect of the invention is characterized in that, the active matrix liquid crystal cell may serve also as a liquid crystal cell of a liquid crystal display device.

According to the second aspect of the invention, the pinpoint-irradiation of the light can be easily attained by making use of the liquid crystal cell of the liquid crystal display device.

According to a third aspect of the present invention, the fingerprint reading device according to the first aspect of the invention is characterized in that, the active matrix liquid crystal cell may be provided in superposition on at least a part of the liquid crystal cell of the liquid crystal display device.

According to the third aspect of the invention, the fingerprint reading sensor is provided integrally with the liquid crystal display

device, and a back light of the liquid crystal display device can be used as an illumination device.

According to a fourth aspect of the present invention, the fingerprint reading device according to any one of the first through third aspects of the invention is characterized in that, the light receiving device may be a line sensor provided along the one side end surface of the light guiding plate.

According to the fourth aspect of the invention, the beams of reflected light are detected sequentially by the line sensor, thereby obtaining the image of the fingerprint.

According to a fifth aspect of the present invention, the fingerprint reading device according to any one of the first through third aspects of the invention is characterized in that, the light receiving device may be constructed of a light receiving element and a lens or a lens array for converging on the light receiving element the light exiting from the one side end surface of the light guiding plate.

According to the fifth aspect of the invention, the beams of reflected light are received sequentially by the photo diode, thereby obtaining the image of the fingerprint.

According to a sixth aspect of the present invention, a fingerprint reading method is characterized in that it comprises the steps of providing an active matrix liquid crystal cell, providing an illumination device for emitting the light from a rear surface

side of the active matrix liquid crystal cell, providing a light guiding plate on a surface side of the active matrix liquid crystal cell, which transmits the light coming from the rear surface side and deflects the light coming from the surface side toward one side end surface, selectively pinpoint-irradiating a fingerprint touching on the surface of the light guiding plate through the active matrix liquid cell with the light coming from a rear surface side of the active matrix liquid crystal cell, receiving the light reflected by the fingerprint and exiting from one side end surface of the light guiding plate, and thus obtaining an image of the fingerprint.

According to the sixth aspect of the invention, the fingerprint is pinpoint-irradiated with the light through the active matrix liquid crystal cell, and the reflected light is received through the light guiding plate, whereby the image of the fingerprint can be easily obtained.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1(a) is a sectional view showing a fingerprint reading device in one embodiment of the present invention; FIG. 1(b) is a plan view thereof; and

FIGS. 2(a) and 2(b) are views showing how detection electrodes of a fingerprint reading sensor of the fingerprint reading device in one embodiment of the present invention are arrayed, and how

a fingerprint is read.

DESCRIPTION OF THE PREFERRED EMBODIMENT

An embodiment of the present invention will hereinafter be described.

FIG. 1 schematically shows a configuration of a fingerprint reading device in one embodiment.

As illustrated in FIG. 1, a finger print reading device 10 has such a geometry that a light guiding plate 12 is disposed above the surface of an active matrix liquid crystal cell 11, a light receiving device 13 is so disposed to be flush with the light guiding plate 12 on its one end side in a side-by-side relation, and an illumination source 14 is disposed on the rear surface side of the liquid crystal cell 11.

Herein, the active matrix liquid crystal cell 11 takes a structure that a first transparent substrate 21 is joined to a second transparent substrate via a spacer 23, and a liquid crystal layer 24 is interposed therebetween. Further, transparent electrodes 25 and active elements 26 are arranged on the inner side of first transparent substrate 21 in a two-dimensional array corresponding to pixels in a face-to-face relation with the liquid crystal layer 24, and an orientated film 27 is provided covering these electrodes 25 and elements 26. On the other hand, on the inner side of the second transparent substrate 22, a common transparent electrode

28 and an oriented film 29 covering the surface thereof are provided above the liquid crystal layer 24. Note that polarizing plates 31, 32 are provided on the outer side of the first and second transparent substrates 21, 22.

The light guiding plate 12 functions to transmit the light emitted from the illumination device 14 toward the surface side but does not transmit the light coming from the surface side toward the rear surface side and guides this flux of light in a plane-direction, whereby the light exits from one side end surface. Further, the light receiving device 13 is constructed of a lens array 15 and a light receiving element 16 such as a photo diode. Note that the lens array 15 may be constructed as a single lens.

Further, the active element 26 is constructed of, e.g., a thin-film transistor (TFT) such as an electric field effect type insulating gate transistor. The above-mentioned active element 26 and transparent electrode 25 may be manufactured by a typical thin-film manufacturing process that has hitherto been known as in the case of a liquid crystal display device. A standard resolution of the fingerprint reading device 10 is on the order of 300 dpi at a pitch of approximately 50 μm . Note that the active element 26 is not limited to the thin-film transistor described above and may be a thin-film diode.

Next, steps of reading a fingerprint by use of the fingerprint reading device 10 will be briefly explained. FIG. 2(a) shows an

array of the transparent electrodes 25 and the active elements 26. FIG. 2(b) schematically shows how the fingerprint is read.

As shown in FIG. 2(a), a source electrode 41 of the transistor serving as the active element 26 is connected to the transparent electrode 25. A gate electrode 42 is connected to a scan line 51. A drain electrode 43 is connected to a signal line 52. A plurality of signal lines 52 are arranged so that the drain electrodes 43 of the respective transistors are connected in series in the X-axis direction. The signal lines 52 are connected to an X-axis driver 53. Further, a plurality of scan lines 51 are arranged so that the gate electrodes 42 of the respective transistors are connected in series in the Y-axis direction. The respective scan lines 51 are connected to the Y-axis driver 54.

Thus, the transparent electrodes 25 are in a state of active addressing via the respective active elements 26. The transparent electrodes 25 are connected to x-pieces of signal lines 52 connected to an X-axis driver 53 and to y-pieces of scan lines 51 connected to a Y-axis driver 54, and have addresses $(1, 1) \sim (x, y)$.

When detecting the fingerprint, to start with, the X-axis driver 53 selects a predetermined signal line 52 and applies a predetermined voltage to a gate electrode 42, in which state a voltage is applied to the active elements 26 arranged in one row through the scan lines 51. The active elements 26, which have been selected after the predetermined voltage has been applied to the gate

electrodes 42, are thereby selected one by one in sequence. The liquid crystal layer 24 in an area facing the selected transparent electrodes 25 for one pixel is oriented, and transmits the light emitted from the illumination device 14.

FIG. 2(b) shows a state at that time. To be more specific, only the selected transparent electrodes 25 for one pixel become transparent, and a finger 60 is thereby illuminated with the light from the illumination device 14. On the other hand, the light reflected by the finger 60 is deflected at a boundary on the rear surface side of the light guiding plate 12, and guided in the plane-direction. The thus guided light is received by the light receiving device 13 provided on one side surface in the side-by-side relation with the light guiding plate 12. This operation is executed with respect to all the pixels, whereby an image of the fingerprint can be obtained.

According to the fingerprint reading device 10 in the embodiment discussed above, the fingerprint can be comparatively easily detected by use of the active matrix liquid crystal cell 11 and the light guiding plate 12. Further, the thus constructed fingerprint reading device 10 takes the structure similar to the liquid crystal structure of the liquid crystal display device, and can be therefore relatively simply manufactured at a low cost. The fingerprint reading device 10 is also easily incorporated together with the liquid crystal panel into an electronic apparatus, etc.

in a way of being attached to the liquid crystal display panel. Namely, the fingerprint reading device described above may easily be incorporated into a variety of electronic apparatuses each having the liquid crystal display device, such as various personal computers, mobile terminals, mobile telephones, personal handyphone systems (PHS) and display-attached cards.

A variety of forms can be conceived in terms of enhancing a handleability when incorporating the fingerprint reading device being thus integral with the liquid crystal panel into the electronic apparatus and saving the installation space. That is, if a resolution of the liquid crystal cell of the liquid crystal display device is almost coincident with that of the fingerprint reading device, the liquid crystal cell and the illumination device and the like can be used completely in common, thereby making it feasible to reduce to a considerable degree the costs of the fingerprint reading device.

Moreover, the fingerprint reading device may be provided in superposition on a part or the whole of the display area of the liquid crystal panel. In this case, for instance, some of the components such as the illumination device, the polarizing plate and so on may be used in common, whereby the costs can be reduced and the installation space can be saved. The fingerprint reading sensor described above is manufactured separately from the thin-film manufacturing process of the liquid crystal panel but may also be

manufactured by the same thin-film manufacturing process. Note that the thus constructed fingerprint reading device may be disposed, without being limited to a specific position in the plane-direction of the liquid crystal display area, at a corner or central portion of the display area, and further the whole display area may also be utilized as the fingerprint reading sensor.

It is to be noted that the light receiving device is constructed of the lens array and the light receiving element in the embodiment discussed above, and may also be constructed as a line sensor provided extending along the whole of one side end surface of the light guiding plate. In this case, the light may be received per pixel as in the embodiment discussed above or received per row of pixels depending on a performance of the light guiding plate.

As discussed above, the present invention exhibits effects in which the image of the fingerprint can be read by use of the active matrix liquid crystal cell and the light guiding plate, and it is also possible to easily incorporate the fingerprint reading device into the liquid crystal display device, enhance the versatility when actually used, increase the productivity and reduce the costs.